



Displays & Controls



FLOW RATE & TOTAL



FT400 Series

6 digit rate; 8 digit total
Flow alarm
Non-volatile memory
Multiple outputs

Flow rate & totalizing display can be wall, meter or panel mounted. Can be external or battery powered & includes a variety of outputs.

BATCH & REGENERATION



FT500 Series

5 digit rate; 8 digit total
Flow alarms
Back-lit display
Units selectable
Multiple outputs

Batch & regeneration controller includes flow rate & totalizing functions.

POWER SUPPLY



PC3, PC12, PC42

Single or dual power supply
Rugged plastic housing
Wall, panel, DIN rail or outlet mounting

Regulated and unregulated, single or dual power supplies with wall, plug-in or DIN rail mounting styles.

DATA LOGGING



DL76

User selected interval
Data storage up to 3yrs
Battery operated
Units selectable

Wall or meter mounted data logger for water usage monitoring & flow management.

DIGITAL COUNTING & TIMING



PT35

Single or dual timers
Bright LED display
Accumulator: 1-9999 pulses
Timer: 1-9999 seconds

Digital timer to control metering pumps or valves in water treatment or chemical dosing applications. Can be used with dry contact or solid state meters.

SIGNAL CONDITIONING



PS40

Splitter output:
3 Transistor
1 Relay

Signal conditioners for dividing & splitting pulses.