



# Low Flow Meters



## PLASTIC MECHANICAL




### SPX/SPT

Flow Rates from 0.07 GPM to 40 GPM  
Pulse Output (Optional 4-20mA)  
Jewel Bearings  
Chemical Resistant

*For metering low-flow chemicals and fertilizers, these mechanical meters are offered with a variety of O-ring and shaft materials to fit your application.*

## STAINLESS MECHANICAL



### SES

Flow Rates from 0.1 GPM to 25 GPM  
Pulse Output (Optional 4-20mA)  
Jewel Bearings

*For low-flow chemical metering, the SES has a high tolerance for problem fluids. Various O-ring and shaft materials are available.*

## LOW FLOW MAGMETER



### PE202

Flow Rates from .03 GPM to 20 GPM  
Pulse and 4-20mA Output  
No Moving Parts  
Chemical & Corrosion Resistant

*The PE202 is designed for low-flow chemical and fertilizer injection or difficult applications with pulsating metering pumps.*

## INSERTION PADDLEWHEEL



### IP800 Series

0.28 - 28 GPM  
1/2" - 8" Pipe Sizes  
Jewel Bearings  
PVC, Polypro, Brass or Stainless Steel

*Bodies are machined from a solid rod for maximum precision. Jewel bearings and nickel-bound tungsten carbide shafts are used for low flow performance.*