

Seametrics



Magmeters



FLANGED FULL-BORE

iMAG 4700 Series

2" - 12" Sizes
External or Battery Powered
2:1 Straight Pipe
Pulse or 4-20mA Output
IP68 & Certified to NSF/ANSI Standard 61
3 Models: 4700, 4700p, 4700r



Unobstructed flow and minimal straight pipe requirements allow these meters to be used where there is little installation space.

BATTERY POWER INSERTION

EX90

4"-12" Pipe Sizes
4 Year Battery Life
No Moving Parts
Saddle or Weld-o-let Models



The EX90 is a battery powered, insertion mag designed for difficult applications where no power is available. With no moving parts, they are low maintenance and easy to install.

PLASTIC FULL-BORE

WMP Series

1" - 3" Sizes
External or Battery Powered
2:1 Straight Pipe
Corrosion Resistant



The polypropylene flow tube offers corrosion resistance to a wide range of fertilizers and chemicals. It's durable and easy to install or remove.

ADJUSTABLE DEPTH INSERTION

EX100/200 Series

3" - 48" Adjustable Depth
Up to 72" Depth Optional
Stainless Steel or Brass
Externally Powered
Hot Tap Available




Easy to install, these meters withstand a variety of temperature, pressure and poor water conditions. With no moving parts, these meters are low maintenance and fit a variety of pipe sizes and types.

FIXED DEPTH INSERTION

EX800 Series

1" - 12" Fixed Depth
Externally Powered
Stainless Steel, PVC or Brass



A choice of materials allows the meter to adapt to a range of temperature, pressure, and corrosive environments.

LOW FLOW FULL-BORE

PE202

1/4" - 3/4" Sizes
Corrosion Resistant
Externally Powered
No Straight Pipe Requirement
Pulse or 4-20mA Output



Easy to install, these meters withstand a variety of temperature, pressure and poor water conditions. With no moving parts, these meters are low maintenance and fit a variety of pipe sizes and types.