



Potable Water Applications



Compliant with the Reduction of Lead in Drinking Water Act (Federal Public Law 111-380)

FLANGED FULL-BORE




IMAG 4700 Series

2" - 12" Sizes
External or Battery Powered
2:1 Straight Pipe
Pulse or 4-20mA Output
IP68 & Certified to NSF/ANSI Standard 61
3 Models: 4700, 4700p, 4700r

Unobstructed flow and minimal straight pipe requirements allow these meters to be used where there is little installation space.



FIXED DEPTH INSERTION



EX800 Series

1" - 12" Fixed Depth
Externally Powered
Stainless Steel, PVC or Brass

A choice of materials allows the meter to adapt to a range of temperature, pressure, and corrosive environments.

BATTERY POWER INSERTION



EX90

4"-12" Pipe Sizes
4 Year Battery Life
No Moving Parts
Saddle or Weld-o-let models

The EX90 is a battery powered, insertion mag designed for difficult applications where no power is available. With no moving parts, they are low maintenance and easy to install.

MULTIJET PULSE




MJN Series

3/4" - 2" Sizes
Multiple Pulse Rates Available
Pulse Rate is Field Changeable
105°F Cold
No Upstream Straight Pipe

This type of meter is known for its wide range, simplicity, and accuracy in low-quality water.

ADJUSTABLE DEPTH INSERTION



EX100/200 Series

3" - 48" Adjustable depth
Stainless Steel or Brass
Externally Powered
Hot Tap Available
NSF-61 (Stainless Only)

With no moving parts, these meters are low maintenance and fit a variety of pipe sizes, types and poor water conditions.