

Multi-Parameter Smart Sensor Adapter



MEASURE AND RECORD

- Conductivity
- pH
- Redox
- Temperature
- TDS
- Salinity
- Level/Pressure
- Specific ions
- and more

Connect up to three AquiStar® Smart Sensors to a single cable to the surface

Features

Adapter Features

- 1.75" (4.4 cm) diameter
- Durable acetal material
- Rugged strain relief at cable connection

Free, Easy-to-Use Software

- Real time viewing
- Batch start and data upload capability
- Table or graph viewing formats for recorded data
- Easy to export to spreadsheets

Smart Sensor Features

- Low power — *2 internal AA batteries*
- External power 12 VDC power option
- 316 SS, fluoropolymer, PTFE construction (titanium optional)
- Modbus® or SDI-12 interface for greater flexibility
- Up to 520,000 records — *depending on sensor*
- Non-volatile memory
- Wireless connectivity — *radios and/or cellular*



TYPICAL INSTALLATION

©2013 Instrumentation Northwest, Inc. All rights reserved. INW and AquiStar are registered trademarks of Instrumentation Northwest. Modbus is a registered trademark of Schneider Electric. Information in this document is subject to change without notice. Doc# 6D0100r3.1 11/5/13



SALES & SERVICE

8902 122nd Avenue NE
Kirkland, WA 98033 USA
425-822-4434
FAX 425-822-8384 / info@inwusa.com



True data, measure by measure

1-800-PRO-WELL
WWW.INWUSA.COM